Opto Engine LLC

MSL-FN-721/1~100mW



SINGLE LONGITUDINAL MODE RED LASER AT 721nm

All solid state single longitudinal mode red laser at 721nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in DNA sequencing, flow cytometry, cell sorting, optical instrument, spectrum analysis, interference, measurement, holography, physics experiment, etc.




SPECIFICATIONS

Wavelength (nm)	721±1	
Operating mode	CW	
Output power (mW)	>1, 5, 10, 20,, 50	>50, , 100
Power stability (rms, over 4 hours)	<3%, <5%	<3%, <5%, <10%
Transverse mode	TEM_{00}	
Longitudinal mode	Single	
Spectral linewidth (nm)	<0.00001	
Coherent length (m)	>50	
Noise of amplitude (rms, 1Hz~20MHz)	<1%, typical<0.5%	
M ² factor	<1.2	
Beam diameter at the aperture (1/e ² , mm)	<1.5	
Beam divergence, full angle (mrad)	<1.2	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate (mm)	27.4	
Operating temperature ($^{\circ}C$)	15~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	





Note: The laser head needs to be used on a heat sink with good heat dissipation.



Opto Engine LLC 7397 Balboa Dr. Midvale, Utah 84047 USA Tel: (801) 553-2253 Email: info@OptoEngine.com Website: www.OptoEngine.com

Data sheet

Rev. 2102