

MLL-III-380/1~150mW



### LOW NOISE UV LASER AT 380 nm

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are used in medical imaging, flow cytometry, DNA sequencing, etc.



### SPECIFICATIONS

Central wavelength (nm)	380±5	
Operating mode	CW	
Output power (mW)	>1, 10, 50, ..., 150	
Power stability (rms, over 4 hours)	<1%, <2% (<0.5%, optional)	
Transverse mode	Multimode	
Noise of amplitude(rms,20Hz~20MHz)	<1%	
Beam diameter at the aperture (1/e <sup>2</sup> ,mm)	<1.5×3.5	
Beam divergence, full angle (mrad)	~2.3×0.2	
Polarization ratio	>50:1 (>100:1, optional) Horizontal±5 degree (Vertical Optional)	
Warm-up time (minutes)	<5	
Beam height from base plate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply	85-264VAC	PSU-III-LED/ PSU-III-FDA (Frequency for 1Hz-30kHz)
	100-240VAC	PSU-A-D (Frequency for 30kHz -100kHz)
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz, 30kHz-100kHz optional	
Expected lifetime (hours)	10000	
Warranty	1 year	



MLL-III-380	PSU-III-LED	PSU-III-FDA	PSU-A-D
<p>143.5(L)×73(W)×46.2(H) mm<sup>3</sup>, 0.7kg</p>	<p>188.6 (L)×155(W)×92 (H) mm<sup>3</sup>, 1.5kg</p>	<p>171(L)×130(W)×62.2 (H) mm<sup>3</sup>, 1.2kg</p>	<p>162(L)×144(W)×70 (H) mm<sup>3</sup>, 1.0kg</p>