

MRL-FN-660/200~400mW

LD PUMPED ALL-SOLID-STATE RED LASER AT 660nm

DPSS red laser at 660nm is made features of ultra compact, long lifetime, low cost and high stability, which is widely used in measurement, spectrum analysis, and scientific research etc.



SPECIFICATIONS

Wavelength (nm)	660±1	
Output power (mW)	>200, 250, 300, ..., 400	
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Warm-up time (minutes)	<10	
M ² factor	<1. 2	
Beam divergence, full angle (mrad)	<1. 5	
Beam diameter at the aperture (mm)	~2. 0	
Beam height from base plate (mm)	27.4	
Polarization ratio	>100:1 (0 or 90 degree)	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC or 5VDC)	PSU-H-LED	PSU-H-FDA
Expected lifetime (hours)	10000	
Warranty	1 year	



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MXL-FN-660	PSU-H-LED	PSU-H-FDA
<p>197(L)×70(W) ×50(H), 2.0 kg</p>	<p>268(L) ×145(W) ×106 (H) mm³, 2.6 kg</p>	<p>238 (L) ×146(W) ×102 (H) mm³, 2.3 kg</p>