

MSL-FN-532/1~400mW



SINGLE LONGITUDINAL MODE GREEN LASER AT 532nm

All solid state single longitudinal mode green laser at 532nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in DNA sequencing, flow cytometry, cell sorting, optical instrument, spectrum analysis, interference, measurement, holography, physics experiment, etc.



SPECIFICATIONS

Wavelength (nm)	532±1	
Operating mode	CW	
Output power (mW)	>1, 5, 10, 20, ... , 300	>300, ..., 400
Power stability (rms, over 4 hours)	<1%, <2%, <3%	<2%, <3%
Transverse mode	TEM ₀₀	
Longitudinal mode	Single	
Spectral linewidth (nm)	<0.00001	
Coherent length (m)	>50	
Noise of amplitude (rms, 1Hz~20MHz)	<0.5%	
M ² factor	<1.2(<1.1 optional)	
Beam diameter at the aperture (1/e ² , mm)	<1.5	
Beam divergence, full angle (mrad)	<1.2	
Polarization ratio	>100:1, Vertical±5 degree (Horizontal Optional)	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate (mm)	27.4	
Operating temperature (°C)	15~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MSL-FN-532	PSU-H-FDA
<p data-bbox="566 1465 817 1484">197(L)×70(W)×50(H) mm³, 1.5 kg</p>	<p data-bbox="1413 1465 1686 1484">275(L) ×145(W) ×104(H) mm³, 2.3 kg</p>